

DMW Execell-Max SAE 5W40

advanced high performance Fully Synthetic engine oil

Product Description:

DMW Execell-Max 5W40 100% Fully Synthetic formulation against friction, heat and corrosion, keeping engines healthy and efficient. DMW additives reduces carbon and sludge build up even under severe driving conditions.

Excellent range of applications; ranging from K class engines to WTI/ VTEC engines to European Engines. Also appropriate for use in turbo-charged cars giving improved engine quietness and reduced emissions. Sustained horsepower and torque throughout the life of your engine with regular use.

Feature and Benefits:

- DMW additives reduces deposits and sludge build up
- Fully synthetic formula provides outstanding wear protection and superior thermal and oxidation stability for extended oil drain interval according to manufacturer recommendation
- excellent cold start properties for fast engine protection

Specifications :

API SN / CF:

ACEA A3 / B3 / B4:

BMW;

Longlife 01; MB 229.5;

VW 502.00 / 505.00;

Porsche

Typical Properties:

SAE Grade:

5W40

TEST	METHOD	UNIT	RESULT
Density @ 15°C	ASTM D4052-09	kg / L	0.85504
Kinematic Viscosity @40°C	ASTM D445-10	cSt	93.00
Kinematic Viscosity @100°C	ASTM D445-10	cSt	14.90
Viscosity Index	ASTM D2270-04		168
Flash Point, COC	ASTM D92-05a (10)	°C	229.0
Pour Point	ASTM D97-09	°C	- 39
Base Number	ASTM D2896-07a	mg KOH/g	8.73

Typical properties are typical of those obtained with normal production tolerance and do not constitute a specification.

All the information contained in this document is considered accurate as of date of printing and no warranty of representation, expressed or implied is made as to the accuracy of the data and information in this publication. The information contained herein is subject to change without notice.